

XPR9TS / XPR9DTS



Standard or Wide Versions

2 POST FLOORPLATE LIFTS



Features include:

- 4000Kg lifting capacity
- Triple reach telescoping front and rear arms
- Double-telescopic screw pad assembly comes as standard
- 4-piece 63 mm stackable adapter set comes standard
- Power unit on either side
- CE Approved and Certified - ETL approved
- Adjustable wide or narrow drive-thru configurations
- Single-piece columns
- Single-point safety release
- Drop-end arms provide a lower pad height
- Electric / hydraulic power system
- Large 510mm x 480mm steel base plates
- Self-lubricating dura-glide polyethylene bearing system
- XPR-9TS - Chain lifting system combined with dual hydraulic cylinders
- XPR-9DTS – Direct drive cylinders
- Single or 3 phase motor



MODEL	XPR 9TS	XPR9DTS
Lifting Capacity (Kg)	4082	4082
Axle Capacity (Kg)	2041	2041
Max Load Per Arm (Kg)	1021	1021
Reach Front & Rear Arms MIN/MAX	698/1308	698/1308
Min Ceiling Height Required (mm)	3020	3833
A. Height Overall (mm)	2870	3683
B. Width Overall (NARROW/WIDE) CONFIG mm	3353/3683	3353/3683
C. Width Outside Columns (NARROW/WIDE) mm	3225/3555	3225/3555
D. Floor Cover Height (mm)	44	44
E. Inside Columns (NARROW/WIDE) CONFIG	2667/2997	2667/2997
J. Min Pad Height (mm)	102	102
K. Rise (mm)	1753	1753
L. Max Lifting Height (mm)	1854-1905	1854-1905
M. Max Lifting Height with 3" Adaptor (mm)	1917-1968	1917-1968
N. Drive Through Clearance (STANDARD/WIDE)	2362/2692	2362/2692
Power Supply (ph/Amps)	1ph or 3ph	1ph or 3ph

5 year structural warranty

