

LES46S	LES46SS
LES46S-42	LES46SS-42
LES55S	LES55SS
LES55S-6	LES55SS-6



**SCISSOR LIFTS**

**Features include:**

- Electro-hydraulic operation
- 4 choices of lifting capacity (3500 - 6000 Kgs)
- 2 choices of platform length (4600 or 5500 mm)
- Large platforms and a sturdy structure, assuring maximum rigidity and stability
- Mechanical locking device with automatic engagement and pneumatic release, ensuring maximum safety
- Hydraulic levelling system by means of a patented synchronisation device assures level lifting of platforms regardless of weight distribution
- Available with Secondary Scissor Lift (SS)
- Surface mounted or recessed installation



**Standard configuration:**

- Free standing control unit is two metres from front right hand platform other configurations are available at additional cost



MODEL	LES46S	LES46S-42	LES55S	LES55S-6	LES46SS	LES46SS-42	LES55SS	LES55SS-6
Capacity	3500	4200	5000	6000	3500	4200	5000	6000
SS Cap	-	-	-	-	3500	3500	4000	4000
Motor KW	2.6	2.6	2.6	2.6	3.5	3.5	3.5	3.5
A. Platform Width (mm)	615	615	615	615	615	615	615	615
B. Width Between (mm)	870	870	870	870	870	870	870	870
C. Overall Width (mm)	2100	2100	2100	2100	2100	2100	2100	2100
D. Overall Length (mm)	4600	4600	5500	5500	4600	4600	5500	5500
E. Overall Length with Run-Up Ramps (mm)	6110	6110	7010	7010	6130	6130	7030	7030
h. Drive On Height (mm)	265	265	265	270	295	295	295	300
H. Lifting Height (mm)	1850	1850	1850	1855	1880	1880	1880	1885
A. SS Platform Length ( mm)	-	-	-	-	2000	2000	2100	2100
B. SS Platform Length ( mm)	-	-	-	-	1390	1390	1390	1390

